

BREAKERMATIC®

Fax

Electronic Protector For Faxes

Ideal for:

- Any model or any brand fax, modems, etc.

BREAKERMATIC Fax is an electronic voltage protector especially designed to prevent damages in your fax machine.

It protects your fax automatically by turning it off, whenever there is a blackout or when the voltage line is too high or too low for the equipment to operate safely. When the voltage returns to its normal level, the protector begins a delay cycle of 5 seconds approximately, before turning the equipment on again. This allows the system to check the correct re-establishment of the line conditions.

BREAKERMATIC Fax also has a peak and transient suppressors required especially for the protection of electronic equipment. These suppressors are located in the voltage feed line as well as in the telephone line.

In its frontal panel, you will find different light signals that show the condition of the line and of the protector. It connects directly to any electrical outlet, which makes its installation very easy. When doing so, your fax will be protected 24 hours a day.

Check the technical specifications on the reverse for more details.



Fax

Leadership and experience in protection and electronic refrigeration control

Models:
PFE-110: Protector for Faxes

Application:
Domestic / Office

Category:
Protector

Installation:

- Unplug your fax from the AC and phone line. Inspect the plugs and receptacles.



- Plug the BREAKERMATIC Fax to the AC receptacle.



- Plug to the BREAKERMATIC your fax, AC and phone line. Then wait 5 seconds.



PFE-110:	CHARACTERISTICS*	MINIMUN	TYPICAL	MAXIMUN	UNITS	TOLERANCES
	Nominal Voltage		120		V r.m.s	
	Output current			10	A r.m.s.	
	Switch type		Dry Relay			
	Transient (AC line)		90		Joules	
	Dissipation (Phone line)		6		Joules	
	Max output power			1000	VA	
	Output voltage range	93		138	V r.m.s	± 2%
	Delay-on-make time		5		Sec.	± 20%
	Response time		1.5		Sec.	± 5%
	Weight		170		grs.	± 10
	Operating temperature range	0		65	°C	

* Technical specifications will vary according to the model and can be changed without notice. PFE-110 / REV. 3 / 01-2006